

Appln No. 10/501,201  
Amdt date March 29, 2007  
Reply to Office action of December 29, 2007

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An energy recovery driving circuit for driving a load with a certain capacitance, comprising:

a resonant inductor ~~connected~~ coupled to the load for alternately allowing a charge ~~and/or current~~ or a discharge current to be applied to the load to flow through the resonant inductor;

a primary coil of a transformer, ~~connected~~ coupled to the resonant inductor, the primary coil being ~~connected~~ coupled to both the resonant inductor and the load so as to alternately allow the charge ~~and/or current~~ or the discharge current to flow through the primary coil when the ~~charging and/or charge current or the~~ discharge current alternately flows through the load through the resonant inductor;

at least one secondary coil of the transformer, coupled to the primary coil; and

an energy recovery unit for generating a current according to the predetermined number of turns of the secondary coil in the secondary coil to allow the current flowing through the secondary coil to be recovered to a supply voltage source.

2. (Currently Amended) The energy recovery driving circuit according to claim 1, wherein the energy recovery unit comprises:

first switching means ~~connected~~ coupled to a supply voltage for receiving a first switching signal to allow a resonance current used to charge the load to flow through the resonant inductor from the supply voltage; and

second switching means ~~connected~~ coupled to ground for receiving a second switching signal to allow a resonance current used to discharge the load to flow through the resonant inductor from the load.

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

3. (Currently Amended) The energy recovery driving circuit according to claim 2, further comprising a sustain driving unit for supplying a sustain voltage to the load;

wherein the sustain driving unit comprises,

third switching means ~~connected~~ coupled between the supply voltage and the load to supply the sustain voltage to the load by reception of a third switching signal after the load is charged by the resonance current used to charge the load,

fourth switching means ~~connected~~ coupled between the ground and the load to apply a ground voltage to the load by reception of a fourth switching signal after the load is discharged by the resonance current used to discharge the load,

a ~~third~~ first body diode ~~connected~~ coupled in parallel with the third switching means to prevent a charged voltage of the load from increasing to be greater than the supply voltage when the load is charged, and

a ~~fourth~~ second body diode ~~connected~~ coupled in parallel with the fourth switching means to prevent a discharged voltage of the load from decreasing to be less than the ground voltage when the load is discharged,

wherein the resonance current is recovered to a supply voltage source through the third body diode after the load is charged to be greater than or equal to the supply voltage, and

the resonance current is recovered to the ground through the fourth body diode after the load is discharged to be less than or equal to the ground voltage.

4. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil is ~~connected~~ coupled between the resonant inductor and the load, the first switching means is ~~connected~~ coupled between the supply voltage and the resonant inductor, and the second switching means is ~~connected~~ coupled between the resonant inductor and the ground;

the energy recovery unit further comprises first and second diodes for conducting a current in a direction of the supply voltage source;

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

the secondary coil comprises;

a first secondary coil ~~connected~~ coupled in series with the first diode between the supply voltage and the ground and coupled to the primary coil so as to allow a charge current to flow through the supply voltage source when the charge current flows through the primary coil, and

a second secondary coil ~~connected~~ coupled in series with the second diode between the supply voltage and the ground and coupled to the primary coil so as to allow a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

5. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to both the first and second switching means, the first switching means is ~~connected~~ coupled between the supply voltage and the primary coil, and the second switching means is ~~connected~~ coupled between the primary coil and the ground;

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground voltage from the ground voltage and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil comprises,

a first secondary coil ~~connected~~ coupled in series with the first diode between the primary coil and the ground, and coupled to the primary coil so as to allow a charge current to flow out from the ground when the charge current flows through the primary coil, and

a second secondary coil ~~connected~~ coupled in series with the second diode between the supply voltage and the primary coil, and the ground voltage and coupled to the primary coil so as to allow a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

6. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to both the first and second switching means, the first switching means is ~~connected~~ coupled between the supply voltage and the primary coil, and the second switching means is ~~connected~~ coupled between the primary coil and the ground;

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil is provided with a first end ~~connected~~ coupled to the primary coil and a second end ~~connected~~ coupled to a common end of the first and second diodes, and is coupled to the primary coil for allowing a charge current to flow out from the ground when the charge current flows through the primary coil and allowing a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

7. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to both the first and second switching means, the first switching means is ~~connected~~ coupled between the supply voltage and the primary coil, and the second switching means is ~~connected~~ coupled between the primary coil and the ground;

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil comprises,

a first secondary coil ~~connected~~ coupled in series with the first diode between a common end of the primary coil and the resonant inductor and the ground, and coupled to the primary coil so as to allow a charge current to flow out from the ground when the charge current flows through the primary coil, and

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

a second secondary coil ~~connected~~ coupled in series with the second diode between the supply voltage and the common end of the primary coil and the resonant inductor, and coupled to the primary coil so as to allow a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

8. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to both the first and second switching means, the first switching means is ~~connected~~ coupled between the supply voltage and the primary coil, and the second switching means is ~~connected~~ coupled between the primary coil and the ground;

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil is ~~connected~~ coupled between a common end of the primary coil and the resonant inductor and a common end of the first and second diodes, and is coupled to the primary coil for allowing a charge current to flow out from the ground when the charge current flows through the primary coil and allowing a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

9. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to the load, the first switching means is ~~connected~~ coupled between the supply voltage and the resonant inductor, and the second switching means is ~~connected~~ coupled between the resonant inductor and the ground;

**Appln No. 10/501,201**  
**Amdt date March 29, 2007**  
**Reply to Office action of December 29, 2007**

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil comprises,

a first secondary coil ~~connected~~ coupled in series with the first diode between a common end of the primary coil and the load and the ground, and coupled to the primary coil so as to allow a charge current to flow out from the ground when the charge current flows through the primary coil, and

a second secondary coil ~~connected~~ coupled in series with the second diode between the supply voltage and the common end of the primary coil and the load, and coupled to the primary coil so as to allow a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

10. (Currently Amended) The energy recovery driving circuit according to claim 3, wherein:

the primary coil has a first end ~~connected~~ coupled to the resonant inductor and a second end ~~connected~~ coupled to the load, the first switching means is ~~connected~~ coupled between the supply voltage and the resonant inductor, and the second switching means is ~~connected~~ coupled between the resonant inductor and the ground;

the energy recovery unit further comprises a first diode for conducting a current in an opposite direction of the ground and a second diode for conducting a current in a direction of the supply voltage; and

the secondary coil is ~~connected~~ coupled between a common end of the primary coil and the load and a common end of the first and second diodes, and is coupled to the primary coil for allowing a charge current to flow out from the ground when the charge current flows through the primary coil and allowing a discharge current to flow into the supply voltage source when the discharge current flows through the primary coil.

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

11. (Previously Presented) The energy recovery driving circuit according to claim 4, wherein the resonant inductor is a leakage inductance of the transformer.

12. (Previously Presented) The energy recovery driving circuit according to claim 4, wherein the number of turns of the secondary coil is greater than or equal to two times that of the primary coil.

13. (Previously Presented) The energy recovery driving circuit according to claim 7, wherein the number of turns of the secondary coil is greater than or equal to that of the primary coil.

14. (Currently Amended) An energy recovery driving circuit for driving a load with a certain capacitance, comprising:

a first resonant inductor ~~connected~~ coupled to the load for alternately allowing a charge ~~and/or~~ current or a discharge current to be applied to the load to flow through the first resonant inductor;

a primary coil of a first transformer, ~~connected~~ coupled to the first resonant inductor, the first transformer primary coil being ~~connected~~ coupled to both the first resonant inductor and the load so as to alternately allow the charge current or the ~~and/or~~ discharge current to flow through the first transformer primary coil when the charge ~~and/or~~ current or the discharge current alternately flows through the load through the first resonant inductor;

at least one secondary coil of the first transformer, coupled to the first transformer primary coil;

a first energy recovery unit for generating a current according to the predetermined number of turns of the first transformer secondary coil in the first transformer secondary coil to allow the current flowing through the first transformer secondary coil to be recovered to a supply voltage source;

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

a second resonant inductor ~~connected~~ coupled to the load for alternately allowing a charge ~~and/or current or a~~ discharge current to be applied to the load to flow through the second resonant inductor;

a primary coil of a second transformer, ~~connected~~ coupled to the second resonant inductor, the second transformer primary coil being ~~connected~~ coupled to ~~both the first resonant inductor and the load~~ through the second resonant inductor so as to alternately allow a charge ~~and/or current or a~~ discharge current to flow through the second transformer primary coil when ~~[[a]] the charge and/or current or the~~ discharge current alternately flows ~~[[into]]~~ through the load through the second resonant inductor;

at least one secondary coil of the second transformer, coupled to the second transformer primary coil; and

a second energy recovery unit for generating a current according to the predetermined number of turns of the second transformer secondary coil in the second transformer secondary coil to allow the current flowing through the second transformer secondary coil to be recovered to the supply voltage source,

wherein the first and second energy recovery units are symmetrically arranged at ~~both~~ respective ends of the load.

15. (Currently Amended) The energy recovery driving circuit according to claim 14, wherein each of the first and second energy recovery units comprises:

first switching means ~~connected~~ coupled to a supply voltage for receiving a first switching signal to allow a resonance current used to charge the load to flow through the resonant inductor from the supply voltage; and

second switching means ~~connected~~ coupled to ground for receiving a second switching signal to allow a resonance current used to discharge the load to flow through the resonant inductor from the load.



**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

16. (Currently Amended) The energy recovery driving circuit according to claim 14, further comprising first and second sustain driving units for supplying a sustain voltage to the load;

wherein the first and second sustain driving units each comprises,

third switching means ~~connected~~ coupled between the supply voltage and the load to supply the sustain voltage to the load by reception of a third switching signal after the load is charged by the resonance current used to charge the load,

fourth switching means ~~connected~~ coupled between the ground and the load to apply a ground voltage to the load by reception of a fourth switching signal after the load is discharged by the resonance current used to discharge the load,

a ~~third~~ first body diode ~~connected~~ coupled in parallel with the third switching means to prevent a charged voltage of the load from increasing to be greater than the supply voltage when the load charged, and

a ~~fourth~~ second body diode ~~connected~~ coupled in parallel with the fourth switching means to prevent a discharged voltage of the load from decreasing to be less than the ground voltage when the load is discharged,

wherein the resonance current is recovered to the supply voltage source through the third body diode after the load is charged to be greater than or equal to the supply voltage,

the resonance current is recovered to the ground through the fourth body diode after the load is discharged to be less than or equal to the ground voltage,

the fourth switching means of the second sustain driving unit is turned on during an operating mode in which the third switching means of the first sustain driving unit is turned on, and

the third switching means of the second sustain driving unit is turned on during an operating mode in which the fourth switching means of the first sustain driving unit is turned on.

17. (Previously Presented) The energy recovery driving circuit according to claim 14, wherein the first transformer having the first transformer primary coil and the first transformer

secondary coil, and the second transformer having the second transformer primary coil and the second transformer secondary coil are integrated into a single transformer.

18. (Original) The energy recovery driving circuit according to claim 3, wherein the fourth switching means is turned on by reception of a charge boosting signal to boost a current of the resonant inductor before a resonance current used to charge the load flows through the fourth switching means, and the third switching means is turned on by reception of a discharge boosting signal to boost the current of the resonant inductor before a resonance current used to discharge the load flows through the third switching means, thus enabling the energy recovery driving circuit to be driven in a current injection manner.

19. (Previously Presented) The energy recovery driving circuit according to claim 5, wherein the resonant inductor is a leakage inductance of the transformer.

20. (Previously Presented) The energy recovery driving circuit according to claim 6, wherein the resonant inductor is a leakage inductance of the transformer.

21. (Previously Presented) The energy recovery driving circuit according to claim 9, wherein the resonant inductor is a leakage inductance of the transformer.

22. (Previously Presented) The energy recovery driving circuit according to claim 10, wherein the resonant inductor is a leakage inductance of the transformer.

23. (Previously Presented) The energy recovery driving circuit according to claim 5, wherein the number of turns of the secondary coil is greater than or equal to two times that of the primary coil.

**Appln No. 10/501,201**

**Amdt date March 29, 2007**

**Reply to Office action of December 29, 2007**

24. (Previously Presented) The energy recovery driving circuit according to claim 6, wherein the number of turns of the secondary coil is greater than or equal to two times that of the primary coil.

25. (Previously Presented) The energy recovery driving circuit according to claim 8, wherein the number of turns of the secondary coil is greater than or equal to that of the primary coil.

26. (Previously Presented) The energy recovery driving circuit according to claim 9, wherein the number of turns of the secondary coil is greater than or equal to that of the primary coil.

27. (Previously Presented) The energy recovery driving circuit according to claim 10, wherein the number of turns of the secondary coil is greater than or equal to that of the primary coil.

28. (Previously Presented) The energy recovery driving circuit according to claim 15, wherein the first transformer having the first transformer primary coil and the first transformer secondary coil, and the second transformer having the second transformer primary coil and the second transformer secondary coil are integrated into a single transformer.

29. (Previously Presented) The energy recovery driving circuit according to claim 16, wherein the first transformer having the first transformer primary coil and the first transformer secondary coil, and the second transformer having the second transformer primary coil and the second transformer secondary coil are integrated into a single transformer.